


PVC Disc Filters



PVC disc filters are used to analysis of metals, silica, and dust in air monitoring. Moisture pick up the level of this filters is low, therefore it is ideal for gravimetric analysis.

Applications **PVC**

- Air monitoring

Features **PVC**

- Pure PVC
- Low ash quantity, ideal for multiple NIOSH analytical methods
- Low moisture pick up the level
- Meets NIOSH and OSHA requirements

Filter Material	Poly Vinyl Chloride (PVC)
Filter Color	White
Filter Surface Type	Plain
Method	ASTM, NIOSH and OSHA
Pore Size	5 μm
Thickness	170-230 μm
Porosity	80%
Ash Content	<1%
Aerosol Retention	99.94%
Air Flow Rate (L/min/cm ²)	2.7
Provided Diameters (mm)	25mm; 37mm; 47mm
Diameters Accuracy	$\pm 0.1\text{mm}$

Order Information

Part Number	Description
PVC-500-2500	PVC Air Monitoring Filter 5 μm 25 mm (100/pk)
PVC-500-3700	PVC Air Monitoring Filter 5 μm 37 mm (100/pk)
PVC-500-4700	PVC Air Monitoring Filter 5 μm 47 mm (100/pk)
PVC-500-2500-P	PVC Air Monitoring Filter 5 μm 25 mm (with supporting pad) (100/pk)
PVC-500-3700-P	PVC Air Monitoring Filter 5 μm 37 mm (with supporting pad) (100/pk)
PVC-500-4700-P	PVC Air Monitoring Filter 5 μm 47 mm (with supporting pad) (100/pk)