

### **NOISE DOSIMETER**





Noise dosimeter with evaluation of band filters and third octave band. It has three simultaneous measurement channels. Compatible with the main standards, it can also evaluate the most suitable hearing protector by assessing noise in octave bands.

**IEC 61252** Electroacoustics - Specifications for personal sound exposure meters

IEC 60804 Integrating-averaging sound level meters

IEC 60651 Sound level meters

IEC 61260 Electroacoustics - Octave-band and fractional-octave-band filters

ANSI S1.25 Specifications for personal noise dosímeters





Octave band and Third Octave band analysis

#### **Includes**

Bivolt charger USB cable Rubber Holster Windscreen Calibration certificate

Can be provided in kits such us (KHO-01 or KHO-08), sold separately.

### **Technical characteristics**

Display: High contrast backlit display

Operating range: 40 to 140 dB

Half-inch microphone with P2 auxiliary input for inserting electrical

signals

Three simultaneous measurement channels

Frequency weight: A, C and Z

Time weight: Fast, Slow and Impulse

Criterion level: 80 to 90 dB Threshold level: 60 to 90 dB Exchange rate: 3, 4, 5 or 6 dB

Results: Dose, projected dose, Leq, Lavg, TWA, LEX 8h, projected LEX 8h

Graphics, histogram, measurements historic

Workday editable

Memory for 60 assessments and around 20.000 registers

Sampling rate: 1 to 60 seconds Automatic acoustic calibration

Agenda function, can program the start, interval and finish of the asses-

sment automatically

High resistence to EMI/RFI

Operating temperature: 0 to 65 °C Operating humidity: 0 to 95 %

Power supply: Li-ion battery 400 mAh

Autonomy: 12 h

Criffer Suite compatible, it can issue customized reports

Dimensions: 90 x 57 x 22 mm

Weight: 79 g



# Occupational hygiene kit

Used to perform great services optimizing the working time the kit KHO-01 is supplied with:

4x Noise dosimeter Sonus 2 Plus 1x Sound calibrator CR-2 1x Carrying case Accessories





## CR-2

Both KHO-01 and KHO-08 kits are supplied with the CR-2 digital sound calibrator. The use of the calibrator is the safest and most accurate way to perform the assessments, minimizing incoherent readings

The CR-2 is class I and complies with **IEC 60942** Electroacoustics - Sound Calibrators



Used to perform great services optimizing the working time the kit KHO-01 is supplied with:

8x Noise dosimeter Sonus 2 Plus 1x Sound calibrator CR-2 1x Carrying case Accessories

The Noise dosimeter and Sound calibrator has a 2 year warranty











